



tesa® 4379 Easy Cover®

Product Information

High Performance Masking Film for Over-Spray Protection

Product Description

tesa® 4379 Easy Cover® is a translucent, polyolefin film that has been specially designed for over-spray protection in combination with a tesa paper and/or fineline masking tape. It is an excellent masking solution for primary and repair paint masking, as well as design painting applications like two-tone fascias or vehicle bodies. tesa® 4379 Easy Cover® allows a single person to cover large areas easily and quickly as well as reducing the logistic complexity.

Benefits:

- Ideal for masking large areas easily and quickly, lightweight and easy to handle
- Paint over-spray adheres well to its embossed surface, ensuring flake-free demasking
- Translucent film allows visual control for easy positioning and quality control, matte finish eliminates reflections
- Excellent resistance against paint solvents, power washing and multiple drying cycles
- Reduction of logistic complexity

Application Fields

- tesa® 4379 Easy Cover® is recommended for professional masking during spray painting work for industrial applications and car body repair
- The 2-in-1 system is ideal for masking large areas easily and quickly
- Excellent protection against spray particles during spray painting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------|-------------------|---------|
| • Backing | PET | • Total thickness | 50.8 µm |
| • Type of adhesive | none | | |



tesa[®] 4379 Easy Cover[®]

Product Information

Additional Information

Standard width is 60" / 1549mm. Custom widths and roll lengths are available upon request.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04379>