



tesa® 4662 Duct Tape

Product Information

Strong duct tape

Product Description

tesa® 4662 is a strong duct tape. It consists of a 27 mesh woven PET/cotton fabric backing coated with a natural rubber adhesive.

Product Features

- Excellent adhesion even on rough and dusty surfaces (e.g. brickwork, timber)
- Water repellent
- Conformable
- tesa® duct 4662 is a self adhesive tape with typical duct features for a wide range of applications.

Application Fields

- Sealing of pipes and ducts
- Bonding of construction and protection films
- Closing of covering foils
- Application on brickwork and timber
- Fixing, closing, packaging and a lot more!

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------------|---------------------|----------|
| • Backing | PE laminated cloth | • Total thickness | 230 µm |
| • Type of adhesive | natural rubber | • Thickness of tape | _NULL µm |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--|------------------------------|
| • Elongation at break | 18 % | • Mesh | 27 threads/inch ² |
| • Tensile strength | 30 N/cm | • Straight tear edge | good |
| • Abrasion resistance | medium | • Temperature resistance | 95 °C |
| • Hand tearability | good | (removability from aluminum after 30 min exposure) | |
| | | • Water resistance | medium |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 4.4 N/cm |
|---------|----------|





tesa® 4662 Duct Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04662>