



tesa® 4688

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PE extruded cloth	• Total thickness	260 µm
• Type of adhesive	natural rubber	• Thickness of tape	_NULL µm
• Type of liner	none		

Properties/Performance Values

• Elongation at break	9 %	• Mesh	55 count per square inch
• Tensile strength	52 N/cm	• Straight tear edges	good
• Abrasion resistance	good	• Temperature resistance	110 °C
• Dielectric breakdown voltage	2900 V	(removability from aluminum after 30 min exposure)	
• Hand tearability	good	• Water resistance	good

Adhesion to Values

• steel	4.5 N/cm
---------	----------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04688>