




tesa® 7379

Product Information



Pure Aluminium Foil Tape

Application Fields

A pure Aluminium foil tape with a paper release liner. Securing heating and cooling lines in refrigeration. Joining and sealing foil faced thermal insulation in roofs and air conditioning. Highly conformable backing ideal for joining reinforced or unreinforced foil faced insulation.

Flame retardant as AS 1530 Part 3-1976

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	aluminium foil	• Total thickness	85 µm
• Type of adhesive	synthetic rubber	• Thickness of tape	_NULL µm
• Type of liner	paper		

Properties/Performance Values

• Elongation at break	5 %	• Hand tearability	very good
• Tensile strength	24 N/cm		

Adhesion to Values

• Steel	12 N/cm
---------	---------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07379>