



tesa® 51485

Product Information



PVC Surface Protection Tape

Product Description

tesa® 51485 is a PVC surface protection tape, comprised of a soft polyvinyl chloride (PVC) backing in combination with a rubber-based adhesive. Due to the durable backing and low tack adhesive with a residue-free removability of up to 6 months tesa® 51485 is ideally for the protection of finished surfaces during fabrication, storage, transportation and installation.

Benefits:

- Durable PVC backing
- Residue-free removability for up to 6 months
- Easy to unwind with low curling characteristics

Application Fields

- tesa® 51485 is recommended for the protection of finished surfaces during fabrication, storage, transportation and installation
- The PVC surface protection tape is particularly suitable for the protection of aluminium window and door frames

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------|----------|-------------------|--------|
| • Backing | PVC film | • Total thickness | 115 µm |
|-----------|----------|-------------------|--------|

Properties/Performance Values

- | | | | |
|-----------------------|-------|--------------------|-----------|
| • Elongation at break | 200 % | • Tensile strength | 24.4 N/cm |
|-----------------------|-------|--------------------|-----------|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 0.8 N/cm |
|---------|----------|



tesa® 51485

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51485>