



tesa[®] 52200

Product Information



75µm PET tape for masking of gasoline particulate filters

Product Description

tesa[®] 52200 is a PET Masking Tape coated with an acrylic adhesive. It is ideal for masking purposes in the production of ceramic gasoline particulate filters.

Main product features are

- High peel strength and excellent wetting on ceramic substrates
- Excellent transparency
- Good shear resistance
- Very good handling performance in converting processes
- Dimension stable when laser engraving
- Removable without residues after drying

Application Fields

Masking of ceramic filters during filling and drying.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | PETP | • Total thickness | 75 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 50 N/cm |
|--------------------|---------|



tesa[®] 52200

Product Information

Additional Information

tesa[®] 52200 has a white paper liner printed with red tesa[®] logo.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52200>