



tesa® 56660

Product Information

Tread Tape

Product Description

tesa® 56660 is an anti slip adhesive tape with a wide range of possible applications. The anti slip tape comprises a PVC substrate coated with aluminium oxide. A strong adhesive mass of acrylate ensures safe footing on the underlying surface. The anti slip effect lasts for up to two years with ordinary use. The particularly abrasion-resistant and resilient adhesive tape has a good resistance against chemicals and salt water, can be torn by hand and removed again without any difficulties. tesa® 56660 is available in the colors black, yellow and black-yellow. The bright yellow and black-yellow colored tapes have a strong visibility for easy identification in areas of safety concerns and for warning purposes, a perfect solution for complementing 5S manufacturing initiatives.

Benefits:

- Durable and slip-resistant backing for applications like industrial floors
- Good adhesion for secure bonding to most surfaces
- Bright yellow and black-yellow colors ensure high visibility for easy identification

Application Fields

- tesa® 56660 is recommended for indoor and outdoor applications
- The anti-slip tape is used for applications in which a secure grip underfoot is required
- tesa® 56660 is a perfect solution for complementing 5S manufacturing initiatives

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------|----------|--------------------|---------|
| • Backing | PVC film | • Type of adhesive | acrylic |
|-----------|----------|--------------------|---------|



tesa® 56660

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=56660>